

SANDBLAST COUPLINGS

Sandblast couplings fit snugly over the cover of G722 sandblast hose and are fastened with screws into the hose carcass. The over-the-cover design allows unimpeded flow of the sand or glass beads, and minimizes coupling wear. Nozzle holders are threaded to accept sand nozzles, and female NPT adapters allow attachment to the machine. Couplings are aluminum or brass and come complete with natural rubber gaskets and screws.

Part Number	Hose I.D.	Hose O.D.	PRICE EACH	Pkg Qty
-------------	-----------	-----------	------------	---------

G75... SANDBLAST COUPLING

G75-075	3/4"	1.50"	\$ 6.80	1
G75-100	1"	1.88"	7.10	1
G75-125	1-1/4"	2.16"	10.60	1
G75-150	1-1/2"	2.38"	14.70	1

G75B... BRASS SANDBLAST COUPLING

G75B-075	3/4"	1.50"	\$ 16.50	1
G75B-100	1"	1.88"	17.10	1
G75B-125	1-1/4"	2.16"	27.00	1
G75B-150	1-1/2"	2.38"	38.60	1

G72... NOZZLE HOLDER

G72-075	3/4"	1.50"	\$ 6.25	1
G72-100	1"	1.88"	7.00	1
G72-125	1-1/4"	2.16"	9.10	1
G72-150	1-1/2"	2.38"	14.00	1

G72B... BRASS NOZZLE HOLDER

G72B-075	3/4"	1.50"	\$ 12.20	1
G72B-100	1"	1.88"	16.60	1
G72B-125	1-1/4"	2.16"	21.40	1
G72B-150	1-1/2"	2.38"	37.80	1

G72M... MALE NPT HOSE END

G72M-050	1/2"	1.06"	\$ 5.70	1
----------	------	-------	---------	---

G77... FEMALE NPT ADAPTER

Pipe Size

G77-125	1-1/4"	\$ 8.90	1
G77-150	1-1/2"	8.90	1

G77B... BRASS FEMALE NPT ADAPTER

G77B-125	1-1/4"	\$ 18.50	1
G77B-150	1-1/2"	18.50	1

G78... GASKET

	Hose Size	Loose	Std Pkg	Pkg
G78	1-1/4"	\$ 1.20	\$ 1.10	10



G75



G75B



G72



G72B



G72M



G77B



G78



G77

Material

ABRASIVE MATERIAL FITTINGS

RHINO EXTERNAL SPLIT FLANGE COUPLINGS

Rhino flanges are sold as sets since the two halves are not identical or interchangeable. They are designed specifically for G743 Rhino Material Transfer Hose and fit tightly over the corrugated cover when the two halves are bolted together. This feature provides secure attachment while allowing full flow. Coupling sets come complete with bolts. Gaskets are purchased separately.

Part Number	Hose I.D.	Hose O.D.	PRICE EACH
G79... ALUMINUM COUPLING SET			
G79-300	3"	4.50"	\$ 189.00
G79-400	4"	5.25"	125.00
G79-600	6"	7.50"	181.00
G79-800	8"	9.50"	345.00
G79-1000	10"	11.50"	525.00
G79-1200	12"	13.75"	819.00



G79

G79M... MALLEABLE IRON COUPLING SET

G79M-400	4"	5.25"	\$ 222.50
G79M-600	6"	7.50"	340.80

G79G... GASKET

G79G-300	3"	4.50"	\$ 12.50
G79G-400	4"	5.25"	21.60
G79G-600	6"	7.50"	26.80
G79G-800	8"	8.50"	41.40
G79G-1000	10"	11.50"	59.20
G79G-1200	12"	13.75"	88.50



G79G

TRI-LOCK FITTINGS

Tri-locks are used where high pressures or dangerous materials require the extra security of a mechanical lock between the fitting and hose. Where a combination nipple can pull out of a hose due to high pressure or end pull, the tri-lock uses a stainless yoke that is locked onto the hose when attached with stainless clamps. Standard plated steel Tri-locks are most often found in hot tar or petroleum applications.

G23T... MALE TRI-LOCK STEM

Part Number	Hose I.D.	PRICE EACH
G23T-300	3"	\$126.40
G23T-400	4"	168.80



G23T